

# Rack Hose

single jacket  
cabinet hose

- 1 1/2" Diameter
- FM approved
- Stock lengths: 50', 75', and 100'
- Pre-folded for ease of installation
- Pin folded to meet cabinet standards
- Emergency use hose only
- Brass or Aluminium Couplings Available



**KEY HOSE**

*"The Hose Company"*

[www.keyhose.com](http://www.keyhose.com)

**Scope:** All polyester single jacket fire hose specifically designed for interior fire fighting use, pin racks, and/or fire cabinets in buildings and plants. NFPA 1961 standards shall be observed in production and assembly to insure quality and durability.

**Jacket Construction:** The jackets will be woven evenly and be free of defects, including knots, lumps, or unsightly disfigurements that could jeopardize the integrity of the hose assembly. The warp and filler yarns shall consist of 100% virgin polyester to reduce weight and increase flexibility.

**Lining:** The lining shall be a single-ply extruded tube of synthetic polyurethane to resist ozone and increase tensile strength characteristics. The polyurethane tube shall adhere to the jacket to prevent delamination. The use of polyurethane lined fire hose is designed to increase packing ability and interior firefighting applications where light weight fire hose is desired.

**Features:**

- FM approved
- Stock lengths: Standard lengths are 50, 75, and 100 feet
- Pre-folded for ease of installation
- 250 PSI working pressure, hydrostatic tested to 500 PSI at point of manufacture
- Available with internal expansion ring brass or aluminum couplings

*Key Hose reserves the right to modify any specification without prior notice to meet or exceed changing standards. Customers are advised special diameters or construction characteristics may be produced by special request. For more information please contact a Key Hose authorized distributor.*

## Performance

Size	Part No.	Service Test	Proof Test	Burst Test	Bowl Size	Weight/ft. Uncoupled
1 1/2"	RR15-500	250 psi	500 psi	750 psi	1 11/16"	.12 lbs.